

Splashbacks - Product Specifications

Colour Selection:

1. Colours should be selected from the Euroglass standard colour range which our technicians carry on them or can be viewed here in our showroom.
2. Colour Matching can be done at an extra cost and time frame of per colour.
3. Limited samples are available when colour selection has been made and a deposit received.
4. Some variation in colour may occur from samples to finished products and from batch to batch and in varying weather conditions when paint is applied and drying.
5. Please note Frost and Etched glass are not suitable for splashback applications.

Site Preparation:

1. Ensure surface is dry and clean. If the surface is a plastered or rendered brick wall ensure the wall is completely dry and sealed, using either a sealed MDF backing board or suitable paint finish.
2. Ensure surface is true and plumb, with maximum dimensional tolerances of +/-2mm. Walls with bows of more than 3mm are unsuitable.
3. Ensure all power points, range hoods and other appliances are fitted in place on the surface ready for an accurate measure.

Installation:

1. Toughened safety glass should be installed in accordance with Australian Standard AS1288-2006.
2. Glass panels should not be installed with the painted surface exposed to environmental pollutants.
3. Use only neutral cure silicone sealants and double sided glazing tape when installing panels.
4. Consideration must be given when measuring and installing glass for manufacturing tolerances. Please refer to site preparation and cutting specification information.
5. An opaque silicone will be used to seal all around glass which is completely enclosed. All open edges of glass are sealed with white paintable gap sealant.
6. Customers are required to be on site at time of installation to approve of colour and pattern prior to fixing to walls.
7. Careful consideration of colour choice is essential as the choice of glass (ie clear or low iron) can effect the final outcome of the colour through the glass. Clear glass has a green tinge and affects light colours. Low iron glass has less green tinge and affects lighter colours less.

Care and Maintenance:

Glass Splashbacks must be kept clean and free of surface build up. General non abrasive household cleaners recommended for glass are suitable as cleaning agents. Sponges, chamois, and cloths may be used, but must be rinsed regularly to remove all foreign particles that could scratch the glass surface. Products like steel wool and scourer pads must be avoided as they may scratch the surface.

